



STORM SHIELD

STORM SHIELD 4 - 6 - 10

STORM SHIELD 12-15

STORM SHIELD 21



STORM SHIELD 4

Seating for 4-8 Adults w/two 6" Vents
Weight: 650 lbs.
Interior L4'-8" x W4'-8" x H5'-5"
Exterior L9'6" x W5'4" x H7'4"
No Concrete ~ 4 Hour Installation.



STORM SHIELD 10

Seating for 10-12 Adults w/three 6" Vents
Weight: 850 lbs.
Interior L6'-11" x W4'-8" x H5'-5"
Exterior L11'9" x W5'4" x H7'4"
No Concrete ~ 4 Hour Installation.



STORM SHIELD 12-15

FLAT GROUND DESIGN
Seats 12-15 Adults w/Ventilation
Weight: 1000 lbs. - Interior L8'8" x W6'10" @
seat H5'8" @walkway H6'10"
Exterior L12'4" x W7'6" x H7'8"
Easy 4-8 hour Installation w/ 2yd ballast or poured concrete.



STORM SHIELD 21

FLAT GROUND DESIGN
Seating for 21 Adults w/ five 6" Vents
Weight: 1500 lbs. - Interior L10' x W6'-10" x @
Seat H5'-8" @walkway H6'-10"
Flat Ground Exterior L11'-6" x W7'-6" x H7'-8"
Easy 4-8 hour Installation w/ 4yd ballast or poured concrete.



STORM SHIELD 6

Seating for 6-10 Adults w/two 6" Vents
Weight: 750 lbs.
Interior L5'-5" x W4'-8" x H5'-5"
Exterior L10'3" x W5'4" x H7'4"
No Concrete ~ 4 Hour Installation.

GENERAL INFORMATION FOR ALL STORM SHIELD 4 - 30

Durable "No Rust" Fiberglass Construction • Mold /
Mildew Resistant Interior • Easy Release Exterior Latch •
• Easy-open Doors with Pneumatic Cylinder • 3 Interior
Latch Points • Stainless Steel Continuous Hinge • Safety
Handrail and Non-Skid Walking Surface on Stairs • Well
Ventilated Compartment - Vents Protected by Ballistic
Tested Door • Carpeted Floor • Comfortable Molded-in
Bench Seating • Reinforced to resist ground water and
total saturation of soil.



STORM SHIELD 12-15

FLAT GROUND DESIGN
Seats 12-15 Adults w/ (3) 6" Vents
Weight: 1000 lbs. - Interior L8'8" x W6'10" @
seat H5'8" @walkway H6'10"
Exterior L8'9" x W7'6" x H7'8"
Easy 4-8 hour Installation w/ 2yd ballast or poured concrete.



STORM SHIELD 30

FLAT GROUND DESIGN
Seating for 30 Adults - Ventilation Exceeds Occupancy
Weight: 2200 lbs. - Interior L15' x W6'10" x @
Seat H5'-8" @walkway H6'
Flat Ground Exterior L16' x W7'6" x H7'8"
Easy 4-8 hour Installation w/ 6yd ballast or poured concrete.